



Our Raised Floor Specification

- 1.Panel Size: 600*600mm 610*610mm
- 2. Made of high quality steel sheet
- 3. Light weight cementitious infilled makes panels solid and quiet
- 4.Completely non-combustible
- 5. Epoxy powder coating for lifetime protection
- 6. Excellent grounding and electrical continutiy
- 7. Excellent rolling load & Ultimate load performance
- 8. Class A flame spread and smoke development rating
- 9. Easy panel installation
- 10.Interchangeable panel strengths
- 11. Finish floor height varies from 40mm to 1500mm



Antistatic HPL Lamination



PVC Lamination



Wood Lamination



Trimless HPL Lamination



Ceramic Lamination

Our Superiority

- 1. Different Surfacce finishes, such as HPL, PVC Vinyl, Ceramic, Marble, Stone, etc
- 2. Most specifications and performances same as bare panels
- 3. Superior anti-static or conductive electricity value
- 4. Excellent grounding and electrical continuity
- 5. All-steel pedestals provide excellent impact load performance



Impact

Loads

7KN

7KN

7KN

7KN

7KN

7KN

7KN

Rolling Loads

10 Times

Passes

2.7KN

3.6KN

4.4KN

5.6KN

6.7KN

8.9KN

11.1KN

10000 Times

1.8KN

2.7KN

3.6KN

4.4KN

5.6KN

6.7KN

8.9KN

Application

Large or medium-sized computer rooms, Data centers, Electrical control romms, Post and telecommunication, etc.



Acc	essories
Standard Stee	l Pedestal FFH=100
Standard Stee	l Pedestal FFH=130
Standard Stee	l Pedestal FFH=150
Standard Stee	l Pedestal FFH=200
Standard Stee	l Pedestal FFH=250
Standard Stee	l Pedestal FFH=300
Standard Stee	l Pedestal FFH=350
Standard Stee	l Pedestal FFH=400
Standard Stee	l Pedestal FFH=450
Standard Stee	l Pedestal FFH=500
Standard Stee	l Pedestal FFH=550
Standard Stee	l Pedestal FFH=600







The good service, The good quality!